



**10K SWING CHECK VALVE** Pressure-Temperature Rating: 1.0 MPa: 180°C

UOB  
UOBM

Parts	UOB	UOBM
Body	SCS13A	SCS14A
Cap	SCS13A/SUS304	SCS14A/SUS316
Disc	SCS13A	SCS14A
Hinge pin	SUS304	SUS316
Plug	SUS304	SUS316
Gasket (for plug)	Asbestos-free sheet	

Face to face dimensions: JIS B2002 \*Except flange thickness  
End flange dimensions: JIS B2220\*  
Wall thickness: KITZ Std.



Nominal Size	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
L	85	95	110	130	150	180	210	240
H	45	55	61	71	72	81	93	104

Unit: mm

**TYPE 200 SWING CHECK VALVE** Pressure-Temperature Rating: 1.0 MPa: 180°C

AKUOM

Parts	AKUOM
Body	CF8M
Cap	CF8M/316
Disc	CF8M
Hinge pin	316
Plug	316
Gasket (for plug)	Aramid fiber

Face to face dimensions: KITZ Std.  
End thread dimensions: ASME B1.20.1  
Wall thickness: KITZ Std.



Nominal Size	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
L	65	80	90	105	120	140	180	200
H	45	55	61	71	72	81	93	104

Unit: mm

**10K LIFT CHECK VALVE** Pressure-Temperature Rating: 1.0 MPa: 180°C

UN

Parts	UN
Body	SCS13A
Cap	SCS13A/SUS304
Disc	SCS13A/SUS304

Face to face dimensions: JIS B2011  
End thread dimensions: JIS B0203  
Wall thickness: KITZ Std.

Nominal Size	3/8	1/2	3/4	1	1 1/4	1 1/2	2
L	55	65	80	90	105	120	140
H	50	53	54	62	66	76	85

Unit: mm