

10K GLOBE VALVE

Pressure-Temperature Rating: 1.0 MPa: 180°C

UJB

UJBM

65 and larger 50 and smaller

Parts	UJB	UJBM
Body	SCS13A	SCS14A
Bonnet	SCS13A	SCS14A
Stem	SUS304 / SCS13A	SUS316
Disc	SUS304	SUS316/SCS14A
Gland	SUS304	SUS316
Gland packing	Refer to Page 10	
Packing nut	SUS304 / SCS13A	
Handwheel	ZDC (10 to 20) / ADC12 (25 to 50) / FCD400 (65 & 80)	
Bonnet ring*	SCS13A	SCS14A
Gasket*	Asbestos-free	
Packing washer	SUS316 (10 to 50)	
Name plate	A1050P	

*For size 2 1/2 and larger

Face to face dimensions: JIS B2011
 End flange dimensions: JIS B2220*
 Wall thickness: KITZ Std.

*Except flange thickness

Nominal Size	Unit: mm								
	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
L	85	85	95	110	130	150	180	210	240
H	109	111	112	142	150	171	189	253	280
D	60	60	70	90	90	100	115	180	225

Type 200 GLOBE VALVE

Pressure-Temperature Rating: 1.0 MPa: 180°C

AKUCLM

Parts	AKUCLM
Body	CF8M
Bonnet	CF8M
Stem	316
Disc	316
Gland	316
Gland packing	Refer to Page 10
Packing nut	CF8
Handwheel	Zinc Diecast (1/4 to 1) / Aluminum Diecast (1 1/4 to 2)
Name plate	Aluminum

Face to face dimensions: KITZ Std.
 End thread dimensions: ASME B1.20.1
 Wall thickness: KITZ Std.

Nominal Size	Unit: mm								
	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	
L	44	48	52	60	72	80	90	100	
H	68	68	68	93	100	122	138	153	
D	55	55	55	60	70	80	90	100	

Type 200 GLOBE VALVE

Pressure-Temperature Rating: 1.0 MPa: 180°C

AKUJM

2 1/2 and larger 2 and smaller

Parts	AKUJM
Body	CF8M
Bonnet	CF8M
Stem	316
Disc	316
Gland	316
Gland packing	Refer to Page 10
Packing nut	304/CF8
Handwheel	Zinc Diecast (3/8 to 3/4) Aluminum Diecast (1 to 2) Ductile iron (2 1/2 to 3)
Bonnet ring*	CF8M
Gasket*	Asbestos-free sheet
Packing washer	316
Name plate	Aluminum

*For size 2 1/2 and larger

Face to face dimensions: KITZ Std.
 End thread dimensions: ASME B1.20.1
 Wall thickness: KITZ Std.

Nominal Size	Unit: mm								
	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
L	55	65	80	90	105	120	140	180	200
H	109	111	112	142	150	171	189	253	280
D	60	60	70	90	90	100	115	180	225